


NORMA**QUICK**® S



Efficient connection of fuel carrying lines



Cannot be opened under pressure due to two locking arms



Designed to connect worldwide standardized spigots as per SAEJ2044 guidelines

QUICK CONNECTORS



NORMAQUICK® S NW

Applications

 $\mathsf{NORMA} \textbf{QUICK}^{\$} \: \mathsf{S} \: \mathsf{connectors} \: \mathsf{are} \: \mathsf{ideal} \: \mathsf{means} \: \mathsf{for} \: \mathsf{connecting} \: \mathsf{fuel} \: \mathsf{lines}.$ They are designed to connect worldwide standardized spigots as per SAEJ2044 guidelines.

| Material | |
|----------|--|
| Housing | PA12-GF50 |
| Retainer | PA12-GF30 |
| O-rings | Inside housing: FPM & FVMQ; on fir tree: FPM |

| Description | ØNW* | Part number | Packaging quantity (ncc) |
|---------------------------|---------|---------------|--------------------------|
| Description | ØI4 4A | Part number | Packaging quantity (pcs) |
| S NW 1/4" - 1/4" - 0° | 1/4" | 0715 6002 006 | 100 |
| S NW 1/4" - 1/4" - 90° | 1/4" | 0715 6001 006 | 100 |
| S NW 5/16" - 5/16" - 0° | 5/16" | 0715 6103 008 | 100 |
| S NW 5/16" - 5/16" - 90° | 5/16" | 0715 6555 008 | 100 |
| S NW 5/16" - 6 mm - 0° | 5/16" | 0715 6509 008 | 100 |
| S NW 5/16" - 6 mm - 90° | 5/16" | 0715 6511 008 | 100 |
| S NW 8 mm - 6 mm - 0° | 8 mm | 0715 6501 008 | 100 |
| S NW 8 mm - 6 mm - 90° | 8 mm | 0715 6502 008 | 100 |
| S NW 3/8" - 6 mm - 0° | 3/8" | 0715 6550 010 | 100 |
| S NW 3/8" - 6 mm - 90° | 3/8" | 0715 6510 010 | 100 |
| S NW 3/8" - 5/16" - 0° | 3/8" | 0715 6509 010 | 100 |
| S NW 3/8" - 5/16" - 90° | 3/8" | 0715 6519 010 | 100 |
| S NW 9.89 mm - 8 mm - 0° | 9.89 mm | 0715 6701 010 | 100 |
| S NW 9.89 mm - 8 mm - 90° | 9.89 mm | 0715 6702 010 | 100 |
| S NW 1/2" - 10 mm - 0° | 1/2" | 0715 6595 012 | 100 |
| S NW 1/2" - 10 mm - 90° | 1/2" | 0715 6596 012 | 100 |
| S NW 1/2" - 12 mm - 0° | 1/2" | 0715 6506 012 | 50 |
| S NW 1/2" - 12 mm - 90° | 1/2" | 0715 6507 012 | 100 |
| S NW 5/8" - 5/8" - 0° | 5/8" | 0715 6501 016 | 100 |
| S NW 5/8" - 5/8" - 90° | 5/8" | 0715 6502 016 | 100 |

^{*} NW (Nominal Width): Diameter of the connecting spigot

Technical benefits

- narrow spaces

NORMAQUICK® S is part of a broad portfolio. Discover more!





NORMAQUICK® SR Single-Lock





Do you have questions or require a personal consultation? Feel free to contact our NORMA Team! Tel.: +49 6181 403-0 Visit our website for more information about our products: norma-connects.com